

EXTERNAL SHROUDS SERIES SPM

The shrouds for cableglands are made in black PVC and they are used to prevent deposits of dust or other substances on the surface of the cablegland and cable entry.

Code	NPT Dimensions	ISO Dimensions
SPM16	3/8"	M16x1.5
SPM1	1/2"	M20x1.5
SPM2	3/4"	M25x1.5
SPM3	1"	M32x1.5
SPM4	1.1/4"	M40x1.5
SPM5	1.1/2"	M50x1.5
SPM6	2"	M63x1.5
SPM7	2.1/2"	M75x1.5
SPM8	3"	M85x1.5
SPM9	3"	M90x1.5



EXTERNAL BLUE SHROUDS SERIES SPMBU

The shrouds for cableglands are made in blue PVC and they are used to prevent deposits of dust or other substances on the surface of the cablegland and cable entry.

Code	NPT Dimensions	ISO Dimensions
SPM16BU	3/8"	M16x1.5
SPM1BU	1/2"	M20x1.5
SPM2BU	3/4"	M25x1.5
SPM3BU	1"	M32x1.5
SPM4BU	1.1/4"	M40x1.5
SPM5BU	1.1/2"	M50x1.5
SPM6BU	2"	M63x1.5
SPM7BU	2.1/2"	M75x1.5
SPM8BU	3"	M85x1.5
SPM9BU	3"	M90x1.5



LOCKNUT SERIES DL

The locknuts are used to hold the cable gland, adaptors or plugs up to the walls of the equipment. Ensure the restraining to the entry of enclosure.

Code	ISO Dimensions	Code	NPT Dimensions
DL16B	M16x1.5	DL38B	3/8"
DL20B	M20x1.5	DL1B	1/2"
DL25B	M25x1.5	DL2B	3/4"
DL32B	M32x1.5	DL3B	1"
DL40B	M40x1.5	DL4B	1.1/4"
DL50B	M50x1.5	DL5B	1.1/2"
DL63B	M63x1.5	DL6B	2"
DL75B	M75x1.5	DL7B	2.1/2"
DL85B	M85x1.5	DL8B	3"
DL90B	M90x1.5	DL9B	3"



Also available in AISI 316L. Code with "s" on final. Example DL20S

EARTHING TAG SERIES ET

The earthing tags are installed between the cable gland and the electrical equipment

Code	ISO Dimensions	Code	NPT Dimensions
ET16B	M16x1.5	ET38B	3/8"
ET20B	M20x1.5	ET1B	1/2"
ET25B	M25x1.5	ET2B	3/4"
ET32B	M32x1.5	ET3B	1"
ET40B	M40x1.5	ET4B	1.1/4"
ET50B	M50x1.5	ET5B	1.1/2"
ET63B	M63x1.5	ET6B	2"
ET75B	M75x1.5	ET7B	2.1/2"
ET85B	M85x1.5	ET8B	3"
ET90B	M90x1.5	ET9B	3"



Also available in AISI 316L. Code with "s" on final. Example ET20S

LOCKNUT SERIES DLC

The locknuts are used to hold the cable gland, adaptors or plugs up to the walls of the equipment. Ensure the restraining to the entry of enclosure.

Code	ISO Dimensions	Code	NPT Dimensions
DLC16B	M16x1.5	DLC38B	3/8"
DLC20B	M20x1.5	DLC1B	1/2"
DLC25B	M25x1.5	DLC2B	3/4"
DLC32B	M32x1.5	DLC3B	1"
DLC40B	M40x1.5	DLC4B	1.1/4"
DLC50B	M50x1.5	DLC5B	1.1/2"
DLC63B	M63x1.5	DLC6B	2"
DLC75B	M75x1.5	DLC7B	2.1/2"
DLC85B	M85x1.5	DLC8B	3"
DLC90B	M90x1.5	DLC9B	3"



Also available in AISI 316L. Code with "s" on final. Example DLC20S

GASKET SERIES SW

Used to obtain the required grade of protection of cable glands. Made in white teflon

Code	ISO Dimensions	Code	NPT Dimensions
SW16T	M16x1.5	SW38T	3/8"
SW20T	M20x1.5	SW1T	1/2"
SW25T	M25x1.5	SW2T	3/4"
SW32T	M32x1.5	SW3T	1"
SW40T	M40x1.5	SW4T	1.1/4"
SW50T	M50x1.5	SW5T	1.1/2"
SW63T	M63x1.5	SW6T	2"
SW75T	M75x1.5	SW7T	2.1/2"
SW85T	M85x1.5	SW8T	3"
SW90T	M90x1.5	SW9T	3"



SERRATED WASHER SERIES SR

The serrated washer are used together with lock nuts to prevent the loose of the attachment. Made in AISI 316L

Code	ISO Dimensions	Code	NPT Dimensions
SR16B	M16x1.5	SR38B	3/8"
SR20B	M20x1.5	SR1B	1/2"
SR25B	M25x1.5	SR2B	3/4"
SR32B	M32x1.5	SR3B	1"
SR40B	M40x1.5	SR4B	1.1/4"
SR50B	M50x1.5	SR5B	1.1/2"
SR63B	M63x1.5	SR6B	2"
SR75B	M75x1.5	SR7B	2.1/2"
SR85B	M85x1.5	SR8B	3"
SR90B	M90x1.5	SR9B	3"



FILLING COMPOUND – BICOMPONENT RESIN REPM-1

Epoxide resin with an excellent resistance grade to chemicals, heat and water. It is available in 50 ml cartridges. It is used as sealant into the cable glands bushing series PMX, PMAX, PMMX and PMFX to prevent the propagation of the flames. Operative temperature: -20°C ÷ +80°C

Cable gland dimension	N° of cable glands filled with one cartridge*
M16x1.5 - 3/8"	25
M20x1.5 - 1/2"	20
M25x1.5 - 3/4"	10
M32x1.5 - 1"	5
M40x1.5 - 1.1/4"	3
M50x1.5 - 1.1/2"	2
M63x1.5 - 2"	1
M70x1.5 - 2.1/2"	1
M85x1.5 - 3"	0.5
M90x1.5 - 3"	0.5



*The value is purely indicative. Ther real number depends on the type and the dimension of the cable used

MANUAL APPLICATOR FOR 50ML CARTIRIDGE SERIES APM50

Using with REPM-1 50ml cartridges. Lightweight, easy to use applicator and easy to load. Usable with one hand. Code: APM50



REPLACEMENT NOZZLE FOR 50ML CARTRIDGES BC-REPM-1

Replacement nozzle for 50ml cartridges. Code: BC-REPM-1



CONDUIT TYPE DMC

Pliable hot deep galvanized steel conduit, reinforced clutch, recoved of smooth grey PVC heavy bore coating and well anchored to the metal conduit

Code	Flexible conduit		Inside bend radius (mm)	Res. to traction	Res. to compression	Temp. range (C°)	Suitable for cable glands series PMS/PMSX	IP rating
	ø int (mm)	ø ext (mm)						
DMC210	10	15,5	50	>1000N	>1250N	-15° ÷ +70°	PMS38 / PMS16	
DMC212	12	18	60	>1000N	>1250N	-15° ÷ +70°	PMS1E / PMS20E	
DMC216	15,5	27	70	>1000N	>1250N	-15° ÷ +70°	PMS1 / PMS20	
DMC221	20,5	27	90	>1000N	>1250N	-15° ÷ +70°	PMS2 / PMS25	
DMC227	26,5	33	120	>1000N	>1250N	-15° ÷ +70°	PMS3 / PMS32	
DMC235	34,5	43	150	>1000N	>1250N	-15° ÷ +70°	PMS4 / PMS40	IP67
DMC240	39,5	48	200	>1000N	>1250N	-15° ÷ +70°	PMS5 / PMS50	
DMC250	50,5	60	250	>1000N	>1250N	-15° ÷ +70°	PMS6 / PMS63	
DMC263	63	73	280	>1000N	>1250N	-15° ÷ +70°	PMS7 / PMS75	
DMC277	77	88	400	>1000N	>1250N	-15° ÷ +70°	PMS8 / PMS85	
DMC102	102	115	480	>1000N	>1250N	-15° ÷ +70°	PMS9 / PMS90	

