

FILLING COMPOUND – BICOMPONENT RESIN REPM-1

Epoxide resin with an excellent resistance grade to chemicals, heat and water. It is available in 50 ml cartridges.

It is used as sealant into the cable glands bushing series PMX, PMAX, PMMX and PMFX to prevent the propagation of the flames.

Operative temperature: $-20^{\circ}\text{C} \div +80^{\circ}\text{C}$

Cable gland dimension	N° of cable glands filled with one cartridge*
M16x1.5 - 3/8"	25
M20x1.5 - 1/2"	20
M25x1.5 - 3/4"	10
M32x1.5 - 1"	5
M40x1.5 - 1.1/4"	3
M50x1.5 - 1.1/2"	2
M63x1.5 - 2"	1
M70x1.5 - 2.1/2"	1
M85x1.5 - 3"	0.5
M90x1.5 - 3"	0.5



**The value is purely indicative. The real number depends on the type and the dimension of the cable used*

MANUAL APPLICATOR FOR 50ML CARTIRIDGE SERIES APM50

Using with REPM-1 50ml cartridges.

Lightweight, easy to use applicator and easy to load.

Usable with one hand.

Code: APM50



REPLACEMENT NOZZLE FOR 50ML CARTRIDGES BC-REPM-1

Replacement nozzle for 50ml cartridges.

Code: BC-REPM-1

