

CONDUIT TYPE DMC

Pliable hot deep galvanized steel conduit, reinforced clutch, recoved of smooth grey PVC heavy bore coating and well anchored to the metal conduit

Code	Flexible conduit		Inside bend radius (mm)	Res. to traction	Res. to compression	Temp. range (C°)	Suitable for cable glands series PMS/PMSX	IP Rating
	ø int (mm)	ø ext (mm)						
DMC210	10	15,5	50	>1000N	>1250N	-15° ÷ +70°	PMS38 / PMS16	IP67
DMC216	15,5	21,5	60	>1000N	>1250N	-15° ÷ +70°	PMS1 / PMS20 PMS1E / PMS20E	IP67
DMC221	26,5	33	90	>1000N	>1250N	-15° ÷ +70°	PMS2 / PMS25	IP67
DMC227	34,5	43	120	>1000N	>1250N	-15° ÷ +70°	PMS3 / PMS32	IP67
DMC235	39,5	48	150	>1000N	>1250N	-15° ÷ +70°	PMS4 / PMS40	IP67
DMC240	50,5	60	200	>1000N	>1250N	-15° ÷ +70°	PMS5 / PMS50	IP67
DMC250	63	73	250	>1000N	>1250N	-15° ÷ +70°	PMS6 / PMS63	IP67
DMC263	77	88	280	>1000N	>1250N	-15° ÷ +70°	PMS7 / PMS75	IP67
DMC277	77	88	400	>1000N	>1250N	-15° ÷ +70°	PMS8 / PMS85 PMS9 / PMS90	IP67

