

ELECTRICAL CONTACTS

Control Unit

Code	Normally Open	Normally Closed	Nominal Current AC15	Nominal Volatage	Cable Section (mm ²)	Features
C1	✓		4A	230V	1.5 ÷ 2.5	
C1AU	✓		4A	230V	1.5 ÷ 2.5	Gold plated
C2		✓	4A	230V	1.5 ÷ 2.5	
C2AU		✓	4A	230V	1.5 ÷ 2.5	Gold plated



Normally open contact

LEDS

Led light

Code	Nominal Current AC15	Nominal Volatage	Cable Section (mm ²)	Colour
CB5	5-20mA	12-30V AC/DC	1.5 ÷ 2.5	○
CB6	5-20mA	12-30V AC/DC	1.5 ÷ 2.5	●
CB7	5-20mA	12-30V AC/DC	1.5 ÷ 2.5	●
CB8	5-20mA	12-30V AC/DC	1.5 ÷ 2.5	●
CB9	5-20mA	12-30V AC/DC	1.5 ÷ 2.5	●
CBB	5-20mA	130-230V AC	1.5 ÷ 2.5	○
CBK	5-20mA	130-230V AC	1.5 ÷ 2.5	●
CBM	5-20mA	130-230V AC	1.5 ÷ 2.5	●
CBS	5-20mA	130-230V AC	1.5 ÷ 2.5	●
CBY	5-20mA	130-230V AC	1.5 ÷ 2.5	●



Led CB6